



- NOTES:**
- Apply ExoAir Primer to all exposed gypsum core prior to application of membrane
 - Slope to the exterior 1/8" per 12"
 - Install reinforcing mesh with 70 wet mils of ExoAir 230, completely covering reinforcing mesh

See securockexoair.com for the most up-to-date product information

This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional

The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.

<p>PERFORMANCE BUILT IN www.securockexoair.com</p>	<p>United States Gypsum Company 550 West Adams Street Chicago, IL 60661</p> <p>USG Technical & Customer Support: 800.USG.4YOU (874-4968)</p>	<p>Tremco Commercial Sealants & Waterproofing 3735 Green Road Beachwood, OH 44122</p> <p>Tremco Technical Support: 866.209.2404</p>	<p>SECUROCK® ExoAir® 430 Panel</p>		<p>File Name: 12789</p>	<p>Rev # 00</p>
			<p>Project: Detail: Offset Application</p>	<p>Drawn by: KAB</p>		